

Work Order ID 102877

June-12-13 9:15:56 AM

\*102877\*

Page 1

Item ID: D3012-5

Accept

\*N900040100\*

Setup Start

\*NS1\*

Revision ID:

Stop

\*NS2\*

Item Name: Decal

Start Date: 6/11/13 Start Qty: 10.00

\*10\*

Cust Item ID:

Required Date: 6/11/13 Req'd Qty: 10.00

\*10\*

Customer:

Reference:

Approvals:

Process Plan: MLC

Date: 13-06-14

Tooling:

Date:

Run Start

\*NR1\*

QC:

Date:

SPC (Y/N):

Date:

Stop

\*NR2\*

Sequence ID/ Work Center ID	Operation Description	Set Up/ Run Hours	Tool ID	Tool #	Plan Code	Accept Qty	Reject Qty	Reject Number	Insp. Stamp
--------------------------------	--------------------------	----------------------	---------	--------	--------------	---------------	---------------	------------------	----------------

Draw Nbr	Revision Nbr	
D3012	Rev A	

100

\*100\*

Purchasing

PURCHASING

Memo

0.00

02/13/06/14 10

Purchasing

Issue P/O: 20161

Make as per Dwg D3012

Manufacture from 3M 7mil masking film p/n 8522CP

Material release note is required

110

\*110\*

Packaging

Receive & Inspect for Damage & Mat'l Certs

0.00

13/06/14 10

Packaging

Memo

0.00

Ensure Material Release Note is attached

120

\*120\*

QC

QC6- Inspect dimensions to drawing

0.00

Quality Control

Memo

0.00

27  
B. 6  
24

10

DQA: \_\_\_\_\_ Date: \_\_\_\_\_



## WORK ORDER NON-CONFORMANCE / UPDATE

QA Closed: \_\_\_\_\_ Date: \_\_\_\_\_

Work Order update only 

Work Order: _____			DISPOSITION			AGAINST DEPARTMENT/PROCESS					
			Rework <input type="checkbox"/>	Skid-tube <input type="checkbox"/>	Crosstube <input type="checkbox"/>	Water Jet <input type="checkbox"/>	Engineering <input type="checkbox"/>				
			Scrap <input type="checkbox"/>	Machining <input type="checkbox"/>	Small Fab <input type="checkbox"/>	Prod. Eng. Coor. <input type="checkbox"/>	Quality <input type="checkbox"/>				
			Use-as-is <input type="checkbox"/>	Thermoforming <input type="checkbox"/>	Finishing <input type="checkbox"/>	Rec/Store/Packaging <input type="checkbox"/>	Other <input type="checkbox"/>				
			Suspected Unapproved <input type="checkbox"/>	Large Fab <input type="checkbox"/>	Composite <input type="checkbox"/>	Supplier <input type="checkbox"/>					

Root Cause	Date	Step	Qty	Description of work order update or non-conformance	Initial Chief Eng	Action Description	Sign & Date	Verification	QC Inspector
Design									
Doc/Data									
Equip/Tooling									
Handling/Pre									
Material									
Operator									
Offset/Setup									
Process									
Supplier									
Training									
Transport									
Unapproved									

## FAULT CATEGORY

Landing Gear	General			
Bending	Bend <input type="checkbox"/>	Folio/Program <input type="checkbox"/>	Outside Dimensions <input type="checkbox"/>	Pressure/Forced <input type="checkbox"/>
Centre Not Concentric	BOM/Route <input type="checkbox"/>	Grain <input type="checkbox"/>	Over/Under tolerance <input type="checkbox"/>	Set-up <input type="checkbox"/>
Cracks	Broken/Damage/Defect <input type="checkbox"/>	Hardware <input type="checkbox"/>	Part Incorrect <input type="checkbox"/>	Temperature/Cure <input type="checkbox"/>
Crimp/Kink/Ripple/Wave	Burrs <input type="checkbox"/>	Inspection Incomplete/Unqualified <input type="checkbox"/>	Part Lost/Missing <input type="checkbox"/>	Weld <input type="checkbox"/>
Cuffs	Contamination <input type="checkbox"/>	Instructions Incomplete/Unclear <input type="checkbox"/>	Part Moved <input type="checkbox"/>	Wrong Stock Pulled <input type="checkbox"/>
Crushing	Countersink <input type="checkbox"/>	Misaligned/off center <input type="checkbox"/>	Positioned Wrong <input type="checkbox"/>	
Heat Treat	Cut Too Short <input type="checkbox"/>	Mislabeled <input type="checkbox"/>	Power Loss/Surge <input type="checkbox"/>	
Inspection Strip in Tube	Drawing <input type="checkbox"/>	Misread <input type="checkbox"/>		
Marks/Chatter	Drill Holes <input type="checkbox"/>	Off-set <input type="checkbox"/>		
Turning Sequence	Finish <input type="checkbox"/>	Out of Calibration <input type="checkbox"/>		
Wave/Twist in Tube	Fit/Function <input type="checkbox"/>	Out of Sequence <input type="checkbox"/>		

Work Order ID 102877

June-12-13 9:15:56 AM

\*102877\*

Page 2

Item ID: D3012-5

Accept

\*N900040100\*

Setup

Start

\*NS1\*

Revision ID:

Item Name: Decal

Stop

\*NS2\*

Start Date: 6/11/13 Start Qty: 10.00

\*10\*

Cust Item ID:

Required Date: 6/11/13 Req'd Qty: 10.00

\*10\*

Customer:

Reference:

Approvals:

Process Plan: \_\_\_\_\_

Date: \_\_\_\_\_

Tooling: \_\_\_\_\_

Date: \_\_\_\_\_

Run

Start

\*NR1\*

QC: \_\_\_\_\_

Date: \_\_\_\_\_

SPC (Y/N): \_\_\_\_\_

Date: \_\_\_\_\_

Stop

\*NR2\*

Sequence ID/  
Work Center ID

Operation  
Description

Set Up/  
Run Hours

Tool ID

Tool #

Plan  
Code

Accept  
Qty

Reject  
Qty

Reject  
Number

Insp.  
Stamp

130

Identify as per dwg & Stock Location: STO23

0.00

\*130\*

Packaging

Packaging

Memo

0.00

10X

11.10.13-06-25

140

QC21- Final Inspection - Work Order Release

0.00

\*140\*

QC

Quality Control

Memo

0.00

13/6/26 JJ

AB0123

DQA: \_\_\_\_\_ Date: \_\_\_\_\_

**WORK ORDER NON-CONFORMANCE / UPDATE**

QA Closed: \_\_\_\_\_

Date: \_\_\_\_\_

Work Order update only 

Work Order: _____	<b>DISPOSITION</b>	<b>AGAINST DEPARTMENT/PROCESS</b>					
Part No. _____	Rework <input type="checkbox"/> Scrap <input type="checkbox"/> Use-as-is <input type="checkbox"/> Suspected Unapproved <input type="checkbox"/>	Skid-tube <input type="checkbox"/> Machining <input type="checkbox"/> Thermoforming <input type="checkbox"/> Large Fab <input type="checkbox"/>	Crosstube <input type="checkbox"/> Small Fab <input type="checkbox"/> Finishing <input type="checkbox"/> Composite <input type="checkbox"/>	Water Jet <input type="checkbox"/> Prod. Eng. Coor. <input type="checkbox"/> Rec/Store/Packaging <input type="checkbox"/> Supplier <input type="checkbox"/>	Engineering <input type="checkbox"/> Quality <input type="checkbox"/> Other <input type="checkbox"/>		
NCR No. _____							

Root Cause	Date	Step	Qty	Description of work order update or non-conformance	Initial Chief Eng	Action Description	Sign & Date	Verification	QC Inspector
Design									
Doc/Data									
Equip/Tooling									
Handling/Pre									
Material									
Operator									
Offset/Setup									
Process									
Supplier									
Training									
Transport									
Unapproved									

**FAULT CATEGORY**

Landing Gear	General				
Bending	Bend <input type="checkbox"/>	Folio/Program <input type="checkbox"/>	Outside Dimensions <input type="checkbox"/>	Pressure/Forced <input type="checkbox"/>	
Centre Not Concentric	BOM/Route <input type="checkbox"/>	Grain <input type="checkbox"/>	Over/Under tolerance <input type="checkbox"/>	Set-up <input type="checkbox"/>	
Cracks	Broken/Damage/Defect <input type="checkbox"/>	Hardware <input type="checkbox"/>	Part Incorrect <input type="checkbox"/>	Temperature/Cure <input type="checkbox"/>	
Crimp/Kink/Ripple/Wave	Burrs <input type="checkbox"/>	Inspection Incomplete/Unqualified <input type="checkbox"/>	Part Lost/Missing <input type="checkbox"/>	Weld <input type="checkbox"/>	
Cuffs	Contamination <input type="checkbox"/>	Instructions Incomplete/Unclear <input type="checkbox"/>	Part Moved <input type="checkbox"/>	Wrong Stock Pulled <input type="checkbox"/>	
Crushing	Countersink <input type="checkbox"/>	Misaligned/off center <input type="checkbox"/>	Positioned Wrong <input type="checkbox"/>		
Heat Treat	Cut Too Short <input type="checkbox"/>	Mislabeled <input type="checkbox"/>	Power Loss/Surge <input type="checkbox"/>	Other <input type="checkbox"/>	
Inspection Strip in Tube	Drawing <input type="checkbox"/>	Misread <input type="checkbox"/>			
Marks/Chatter	Drill Holes <input type="checkbox"/>	Off-set <input type="checkbox"/>			
Turning Sequence	Finish <input type="checkbox"/>	Out of Calibration <input type="checkbox"/>			
Wave/Twist in Tube	Fit/Function <input type="checkbox"/>	Out of Sequence <input type="checkbox"/>			



DESIGN	DRAWN BY	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKED	APPROVED	DRAWING NO.	REV. A
		D3012	SHEET 1 OF 1
DATE	TITLE	SCALE	
01.03.30	DECAL	1:1	
A	01.03.30	NEW ISSUE	

RELEASED  
01.04.01 off

- POINT A -  
SWL=300lb/136kg  
DO NOT USE WITH POINT B  
P/N D3012-1

D3012-1

- POINT B -  
SWL=500lb/227kg  
DO NOT USE WITH POINT A OR C  
P/N D3012-3

D3012-3

- POINT C -  
SWL=300lb/136kg  
DO NOT USE WITH POINT B  
P/N D3012-5

D3012-5

102877-1326-14  
R  
DOCS  
COPY  
PRINT  
01/04/01  
A

MATERIAL: WHITE LETTERS ON BLACK ADHESIVE BACK  
MANUFACTURED FROM 3M 7 MIL MASKING FILM #8522CP

Copyright © 2001 by DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.

# Studio de Lettrage

**210 Main Street W  
Hawkesbury, Ontario K6A 2H6**

**INVOICE**

Invoice No.: 20311  
Date: 06/21/2013  
Ship Date:  
Page: 1  
Re: Order No. WO10206

**Sold to:**

**Ship to:**

**Dart Aerospace Ltd**  
1270 Aberdeen  
Hawkesbury, Ontario K6A 1K7

Dart Aerospace Ltd  
Hawkesbury, Ontario

**Business No.:** 82500 7651 RT0001

\*\*\*\*Certificate of Conformity\*\*\*\*

Customer:

Studio Letterage

Purchase Order #:	Packing Slip #:	Part #:	Serial #:
20101	W010206		

## PRODUCT DATA SHEET



### Avery® IPM™ 2031

issued: 01/04/2005

#### Introduction

Avery® IPM™ 2031 is a high quality pressure-sensitive vinyl film, designed for use on wide format inkjet printers. Avery® IPM™ 2031 has excellent printing properties, allowing crisp print quality with bright and vibrant colours. Avery® IPM™ 2031 offers rapid ink drying and a water-resistant material. It combines good adhesion during its life and easy removal afterwards.

#### Description

Facefilm: 80-micron premium white calendered, topcoated vinyl.

Adhesive: removable, acrylic based

Backing paper: one side coated kraft paper, 140 g/m<sup>2</sup>

#### Features

- Excellent printability
- Vibrant and bright colours
- Crisp print quality
- Spray water resistant with specific pigmented inks
- Good adhesion, excellent removability
- Warranty on outdoor durability

#### Recommendations for use

A wide variety of full-colour graphics for indoor - and **short/medium term outdoor** applications such as posters, murals, displays, exhibition stands, vehicle graphics etc. Avery® IPM™ 2031 is suitable for application to a wide variety of substrates and will remove cleanly for up to 1 year after application.

IPM media should be handled with care as any surface contamination may affect the print quality. Media should be processed in an environment of 15-25°C and 30-70% relative humidity. After drying, the finished prints should be wrapped in polyethylene film and despatched flat or rolled with the printed side facing outwards. To protect prints against water, UV/light and abrasion, overlamination with a clear film is recommended. For specific details of Avery® DOL combinations, refer to "Technical Bulletin 5.3. Recommended combinations of Avery® Overlaminate and Avery® Digital Print Media".

**Always test your combination of Avery® IPM™ medium, inkjet printer and inks prior to commercial use.**

#### Compatibility

Avery® IPM™ 2031 is compatible with a broad selection of inkjet printers, when printing with pigmented, water based inks. For specific details refer to "Technical Bulletin 5.6 Avery Dennison Inkjet Print Media - Printer compatibility".

#### Durability:

Avery® IPM™ 2031 is warranted for outdoor use in conjunction with pigmented outdoor inks from HP, Encad and Colorsprint. The warranted period varies from type of application and type of overlaminates from 18 months up to 5 years. For full details, see our Avery® IPM™ Outdoor warranty.



[www.averygraphics.com](http://www.averygraphics.com)

Graphics Division  
Rijndijk 86, P.O. Box 118  
2394 ZG Hazerswoude - The Netherlands  
Tel +31 71 3421500 - Fax +31 71 3421538

## PRODUCT CHARACTERISTICS

Avery® IPM™ 2031

### Physical properties

Features	Test method <sup>1</sup>	Results
Caliper, facefilm	ISO 534	80 µm
Gloss	ISO 2813, 20°	1%
Dimensional stability	DIN 30646	0.3 mm. max
Adhesion, initial	FINAT FTM-1, stainless steel	180 N/m
Adhesion, ultimate	FINAT FTM-1, stainless steel	260 N/m
Flammability		Self extinguishing
Accelerating ageing	DIN 53587, 500h exposure	No negative impact on film
Shelf life	Stored at 22° C/50-55 % RH	Performance
Removability		2 years
Not when applied to: Nitro-cellulose paints, ABS, Polystyrene, certain types of PVC		
Durability <sup>2</sup>	Overlaminated with DOL 4300 Overlaminated with DOL 1000, DOL 1100 with overlaps Overlaminated without overlaps for static applications only Without overlamine and used for static, Non-abrasive application ONLY	5 years 3 years 2 years 18 months

Only when printed with ENCAD GO, HP and Colorsprint pigmented inks and when properly applied in accordance with our application instructions. Only applicable for vertical exposure.

### Temperature range

Features	Results
Application temperature	Minimum: +10°C
Service temperature	-20°C to +80°C

### Important

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

All technical data are subject to change. In case of any ambiguities or differences between the English and foreign versions of these Conditions, the English version shall be controlling.

### Warranty

Avery® branded materials are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give any guarantee, warranty, or make any representation contrary to the foregoing.

All Avery® branded materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

#### 1) Test methods

More information about our test methods can be found on our website.

#### 2) Durability

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.



[www.averygraphics.com](http://www.averygraphics.com)

Graphics Division  
Rijndijk 86, P.O. Box 118  
2394 ZG Hazerswoude - The Netherlands  
Tel: +31 71 3421500 - Fax: +31 71 3421538